



TECHNISTAR S6 Int. Edt.

HDTV digital satellite receiver with USB-PVR function

EAN	Item no.
4019588647176	0006/4717

CONNECTIONS	Teletext: Yes	Internet radio: Yes
USB: 1 (USB 2.0)	Sleep timer: Yes	TECHNIROUTER ready: Yes
Common Interface Plus (CI+): Yes	Media Player: Yes	Tuner type: DigitalSat
DC IN: 1	HOTEL MODE	Satellite radio: Yes
audio/video output analog (3.5 mm jack): Yes TechniSat specific adapter set necessary (available at 0000/3649)	Control panel lock: Yes	Single Cable Solution (SatCR): SCR1 = EN50494, SCR2 = EN50607
Digital electric audio output: Yes	Protected access to hotel mode: Yes	DVB-S tuner: 1
HDMI (out): 1	Selectable start channel: Yes	TUNER - SAT
F socket: Yes	Menu locking: Yes	DVB-S: QPSK
Smartcard reader: Yes	Selectable start source: Yes	FEC: Viterbi and Reed-Solomon
Ethernet 10/100 (RJ-45): Yes	Customisable start screen: Yes	Reception range: 950 ... 2150 MHz
DECODER	Integrated LED clock: Yes	DVB-S2: 8PSK - QPSK
Video decoder: MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC	Lockable volume: Yes	Viterbi rates: 1/2, 2/3, 3/4, 5/6, 7/8
Audio decoder: MPEG-1 & MPEG-2 Layer I, II, III	OTHER FEATURES	DVB-S: 2 ... 45 Mbaud
DECRYPTION SYSTEM	OSD languages: Swedish, Russian, Danish, English, Dutch, Norwegian, French, Czech, Italian, Turkish, Hungarian, German, Spanish, Polish, Portuguese, Greek	DVB-S2: 2 ... 45 Mbaud
CI+: Yes (v1.3)	Regional channel selection: Yes	INTERNET/NETWORK
Conax: Yes	Total programme memory: 9999	int_speedtest: Yes
DISPLAY	Internet radio: Yes	LNB CONTROL
1080i: Yes	POWER CONSUMPTION	DiSEqC: 1.0 / 1.2
720p: Yes	In operation: 4.8 W without LNB	Horizontal: 18 V
HD: Yes	Standby: < 0,3 W	Band switch: 22 kHz
SD: Yes	POWER SUPPLY	Current consumption: 400 mA
576p: Yes	Nominal voltage: 230 V	Vertical: 14 V
576i: Yes	Frequency: 50 Hz	MULTIMEDIA
Freeze frame: Yes	Mains adapter: external DC 12V/2A	Recordings edition function: Yes
Type: 7 segment, 4 digits, white	SUPPORTED FORMATS & CODECS	Recordings folder management: Yes
1080p: Yes	Picture-Formats: TIFF, GIF, PNG, JPEG, BMP	DVR function: Ja
ENVIRONMENT	Video-Formats: Xvid, ASF, TS, MPG, MP4, TS4, MOV, M4V, AVI, MKV, M2TS	DVR storage medium: via USB
Ambient temperature: 5 ... 35 °C	Audio-Formats: MP2, MP3, AIFF, DDAC3, FLAC, AAC, WAV, OGG	Timeshift: Yes
Humidity: 10 ... 75 %	Video-Codex: MPEG-4, H.264, MPEG-2	TECHNISAT ADDED VALUE SERVICES
Storage temperature: -20 ... 60 °C	TECHNISAT CONNECT	SFI: Yes
HANDLING/COMFORT	SFI: Yes	AUTOINSTALL: Yes
Page memory: 1000	Control: Yes	ISIPRO: Yes
Clock: Yes	TUNER	TECHNIFAMILY: Yes
Teletext subtitles: Yes		SCOPE OF DELIVERY

KEYFEATURES

Pay TV ready	ISI Mode	AutoInstall
Universal Plug And Play (UPnP)	Editing function	"SiehFern INFO" (SFI)
Perfect Recording	ISIPRO	
TechniRouter-ready	TechniFamily	