



SATMAN 850 PLUS

SATMAN external unit with pre-assembled AZ/EL mount, 85 cm Ø

EAN	Item no.	Colour	Box	Weight (Box)	Weight
4019588858848	6085/8804	brick/red	88.00 x 95.00 x 24.00 cm		
4019588858077	6085/8807	polar/white			
4019588858855	6085/8805	yellow with Smiley	88.00 x 95.00 x 24.00 cm	8.6 kg	5 kg
4019588858824	6085/8882	beige	88.00 x 95.00 x 24.00 cm	8.8 kg	5.2 kg
4019588858220	6285/8882	fir/green	88.00 x 95.00 x 24.00 cm	8.8 kg	5.2 kg
4019588858206	6385/8882	slate/grey	88.00 x 95.00 x 24.00 cm	8.8 kg	5.2 kg
4019588858244	6485/8882	brick/red	88.00 x 95.00 x 24.00 cm		
4019588858275	6785/8882	polar/white			
4019588588820	6585/8882	yellow with Smiley	87.00 x 95.00 x 24.00 cm	8.8 kg	5.2 kg
4019588828827	6285/8880	fir/green	88.00 x 95.00 x 24.00 cm	8.8 kg	5.2 kg
4019588848887	6485/8880	brick/red	88.00 x 95.00 x 24.00 cm	8.8 kg	5.2 kg
4019588858879	6785/8880	polar/white			
4019588855885	6585/8880	yellow with Smiley	87.00 x 95.00 x 24.00 cm	8.8 kg	5.2 kg
4019588189805	6085/8980	beige	88.00 x 95.00 x 24.00 cm	8.8 kg	5.2 kg
4019588858978	6785/8980	polar/white			

LOCAL OSCILLATOR
High band: 10.7 GHz
Horizontal: 16 - 19 V
Low band: 9.75 GHz
Vertical: 11,5 - 14,5 V
GENERAL CHARACTERISTICS
Material strength: 1.6 mm
Top features: Ideal for wall and roof mounting
Top features: 1 orbital position (for example Astra 19.2° East)
Top features: For distribution to multiple participants on demand, TechniSat distribution elements are required
Coating: Powder-coated on both sites
Material: Aluminium

Top features: For 1 to multiple participants
INPUT FREQUENCY RANGE
High band: 11.7 ... 12.75 GHz
Low band: 10.7 ... 11.7 GHz
NOISE FACTOR
Upper frequency range: 0.6 dB max.
Lower frequency range: 0.6 dB max.
OUTPUT FREQUENCY RANGE
Low band: 950 ... 1950 MHz
High band: 1100 ... 2150 MHz
PREPARED FOR
Number of orbit positions: 1
TECHNICAL DATA
Gain: 38.2 dBi @11,3 GHz

Rated measurement: 0.85 m
G/T: 17.2 dB/K
Feed reception: pour UNYSAT-Universal-LNB
Mast Ø: 65 mm max.
F/D: 0.67
Offset angle: 21 °
SCOPE OF DELIVERY
Satellite dish antenna SATMAN 850, AZ/EL bracket mount, LNB in weather-proof housing, screws, installation instructions

UNYSAT Universal-V/H-LNB

ARTICLE INFORMATION

KEYFEATURES

1 subscriber	Multiple subscribers	2 subscribers
1 orbit position	HDTV	4 subscribers

Testurteil(e) SATMAN 850 PLUS



Note: Gut | 88,7 %
SATVISION (04/2012)



Zweiter Platz in der
Kategorie Sat-Anlagen bei
der Leserwahl zum König-
Kunde-Award 2014
(Camping, Cars & Caravans)