



SKYRIDER 65 Twin

Automatic digital satellite reception system for camper vans/mobile homes

EAN	Colour	Item no.
4019588255821	yellow with Smiley	2565/1582
4019588275829	polar white	2765/1582

AMBIENT OPERATING CONDITIONS	INPUT FREQUENCY RANGE	F/D: 0.6
IP class: X 6	Low band: 10.7 - 11.7 GHz	G/T: 14.5 dB/K
Ambient temperature: -20 ... 60 °C	High band: 11.7 - 12.75 GHz	Offset angle: 27 ° (EL 0 ~ 145° / AZ 390°)
LOCAL OSCILLATOR	NOISE FACTOR	Gain: 35.7 dBi
Low band: 9.75 GHz	Noise figure: typ. 0.7 dB	Amplification: 55 ... 65 dB
High band: 10.6 GHz	OUTPUT FREQUENCY RANGE	Connector type: F socket
LNB CONTROL	Low band: 950 - 1950 MHz	SCOPE OF DELIVERY
DiSEqC: 1.0 / 1.1	High band: 1100 - 2150 MHz	Automatic control unit for SKYRIDER 65, single LNB, assembly instructions, mounting plate, controller, remote control, 2 x F-type SAT cable, 12 volt adapter cable, roof gasket
Vertical: 10.5 ~ 14.5 V	POWER CONSUMPTION	
Horizontal: 15.5 ~ 21 V	In operation: 50 W / 4 A max. (während der Satellitensuche)	
DIMENSIONS / WEIGHT	POWER SUPPLY	
Device height (retracted): 175 mm	Nominal voltage: DC 12 V	
Device height (extended): 980 mm	PREPARED FOR	
GENERAL CHARACTERISTICS	Number of clients: 2	
Material: plastic / metal	Number of orbit positions: 10	
HANDLING/COMFORT	TECHNICAL DATA	
Satellite search time: Bis zu 180 s (typisch)	Outputs: 2	
Maximum permissible speed: 130 km/h		

KEYFEATURES	
HDTV	Camping 2 subscribers