



SKYRIDER DOME Single

Compact, mobile digital satellite system with single LNB

| EAN | Item no. |
|---------------|-----------|
| 4019588145801 | 0145/1580 |

| | | |
|-----------------------------------------------|-------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| LOCAL OSCILLATOR | Low band: 10.7 - 11.7 GHz | Outputs: 1 |
| Low band: 9.75 GHz | High band: 11.7 - 12.75 GHz | F/D: 0.23 |
| High band: 10.6 GHz | OUTPUT FREQUENCY RANGE | G/T: 9.7 dB/K |
| LNB CONTROL | Low band: 950 - 1950 MHz | Gain: 31 dBi |
| DiSEqC: 1.0 / 1.1 | High band: 1100 - 2150 MHz | Connector type: F socket |
| Vertical: 10.5 ~ 14.5 V | POWER CONSUMPTION | SCOPE OF DELIVERY |
| Horizontal: 15.5 ~ 21 V | In operation: 30 W max. (während der Satellitensuche) | SKYRIDER Dome, instruction manual, controller, remote control, 2 x F-type SAT cable, 12 volt adapter cable |
| AMBIENT OPERATING CONDITIONS | POWER SUPPLY | |
| IP class: X 6 | Nominal voltage: DC 12 ... 24 V | |
| Ambient temperature: -20 ... 60 °C | Power consumption: 170 mA (LNB) | |
| GENERAL CHARACTERISTICS | Effective output: 18 W / 1,5 A max. | |
| Material: plastic | PREPARED FOR | |
| HANDLING/COMFORT | Number of clients: 1 | |
| Satellite search time: Bis zu 180 s (typisch) | Number of orbit positions: 4 | |
| INPUT FREQUENCY RANGE | TECHNICAL DATA | |

| KEYFEATURES | | |
|-------------|--------------|--|
| HDTV | Camping | |
| | 1 subscriber | |