



DIGIDISH 45 (aluminium), Universal-V/H-LNB

Thanks to its ingenious reflector design the reception performance of the DigiDish 45 is better than with many 60 cm mirrors - and that is with a far lower size of reflector.

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588458949	1045/8194	beige	3.5 kg	2.7 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588453944	1345/8194	slate/grey	3.5 kg	2.7 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588441941	1445/8194	brick/red	3.5 kg	2.7 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588471948	1745/8194	polar/white			45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm

TOP FEATURES

Only 45 cm small

1 or 2 participants

1 orbital position (for example Astra 19.2 ° East)

Especially suitable for balcony installation / Ideal for the city

Ideal for ground and wall mounting

Also available as a complete package including digital satellite receiver

LOCAL OSCILLATOR

Low band: 9.75 GHz

High band: 10.7 GHz

LNB CONTROL

Vertical: 11,5 - 14 V

Horizontal: 16 - 19 V

Band switch: 22 kHz

INPUT FREQUENCY RANGE

Low band: 10.7 ... 11.7 GHz

High band: 11.7 ... 12.75 GHz

NOISE FACTOR

Lower frequency range: 0.7 dB max.

Upper frequency range: 0.7 dB max.

OUTPUT FREQUENCY RANGE

Low band: 950 - 1950 MHz

High band: 1100 - 2150 MHz

POWER SUPPLY

LNB voltage supply: 11.5 ... 19 V

Power consumption: max. 190 mA

PREPARED FOR

Number of orbit positions: 1

Number of clients: 1

TECHNICAL DATA

Rated measurement: 0.45 m

F/D: 0.6

Gain: 32.2 dBi @11,3 GHz

Offset angle: 30 °

Feed reception: 40 mm

SCOPE OF DELIVERY

Satellite dish 45 cm, LNB, wall bracket, screws, tool, mounting instruction

Universal-V/H-LNB

Testurteil(e) DIGIDISH 45 (aluminium), Universal-V/H-LNB



Zweiter Platz in der Kategorie Sat-Anlagen bei der Leserwahl zum König-Kunde-Award 2014 (Camping, Cars & Caravans)