



TECHNISTAR S6 Int. Edt.

HDTV digital satellite receiver with USB-PVR function

| EAN | Colour | Item no. | Weight (Box) | Weight | Device (W x H x D) | Box |
|---------------|--------|-----------|--------------|--------|-------------------------|-------------------------|
| 4019588647176 | black | 0006/4717 | 1.24 kg | 600 g | 22.00 x 4.50 x 17.70 cm | 31.00 x 8.00 x 19.50 cm |

TOP FEATURES

HDTV tuner (DVB-S/S2)

DVRready: Digital video recorder function for recording to USB hard drive

Timeshift in connection with USB hard drive

Operation on 12V

Multimedia streaming on home network (via UPnP, server)

Electronic program guide (EPG)

MULTIMEDIA

DVR function : Ja

DVR storage medium : via USB

Timeshift : Yes

Recordings edition function : Yes

Recordings folder management : Yes

USB : 1 (USB 2.0)

Common Interface Plus (CI+) : Yes

Smartcard reader : Yes

Digital electric audio output (S/PDIF) : Yes
audio/video output analog (3.5 mm jack) :
Yes TechniSat specific adapter set
necessary (available at 0000/3649)

Ethernet 10/100 (RJ-45) : Yes

F socket : 1

DC IN : 1

DECODER

Video decoder : MPEG-2 MP@HL/ML,
H.264/MPEG-4 AVC

Audio decoder : MPEG-1 & MPEG-2 Layer I,
II, III

DECRYPTION SYSTEM

Conax : Yes

CI+ : Yes (v1.3)

DISPLAY

Freeze frame : Yes

SD : Yes

HD : Yes

1080p : Yes

1080i : Yes

720p : Yes

576p : Yes

576i : Yes

Type : 7 segment, 4 digits, white

HANDLING/COMFORT

Page memory : 1000

Teletext subtitles : Yes

Media Player : Yes

Channel presets : 9999

Teletext : Yes

Clock : Yes

Sleep timer : Yes

HOTEL MODE

Protected access to hotel mode : Yes

Customisable start screen : Yes

Lockable volume : Yes

Menu locking : Yes

Control panel lock : Yes

Integrated LED clock : Yes

Selectable start source : Yes

Selectable start channel : Yes

AMBIENT OPERATING CONDITIONS

Ambient temperature : 5 ... 35 °C

Humidity : 10 ... 75 %

LNB CONTROL

Vertical : 14 V

Horizontal : 18 V

Band switch : 22 kHz

Current consumption : 400 mA

DiSEqC : 1.0 / 1.2

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

TECHNIFAMILY : Yes

SFI : Yes

ISIPRO : Yes

INTERNET/NETWORK

Internet speed test : Yes

AUDIO

audio_klare_sprache : Yes über DVB

CONNECTIONS

HDMI™ (out) : 1

| | | |
|---|--|---|
| OTHER FEATURES | STREAMING | TUNER |
| OSD languages : German, Danish, English, French, Greek, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian | Cloud store : Ja | Tuner type : DigitalSat |
| Regional channel selection : Yes | DLNA Client : Yes | DVB-S tuner : 1 |
| Internet radio : Yes | SUPPORTED FORMATS & CODECS | Single Cable Solution (SatCR) : SCR1 = EN50494, SCR2 = EN50607 |
| POWER CONSUMPTION | Video-Codecs : MPEG-2, MPEG-4, H.264 | Satellite radio : Yes |
| In operation : 4.8 W without LNB | Video-Formats : M4V, MP4, MKV, MOV, MPG, TS, TS4, Xvid, M2TS, AVI, ASF | Internet radio : Yes |
| Standby : < 0,3 W | Picture-Formats : BMP, JPEG, GIF, PNG, TIFF | Reception on : HD-TV, SD-TV, DVB radio |
| POWER SUPPLY | Audio-Formats : WAV, MP3, AAC, FLAC, MP2, OGG, DDAC3, AIFF | TECHNIROUTER ready : Yes |
| Nominal voltage : 230 V | TECHNISAT CONNECT | TUNER - SAT |
| Frequency : 50 Hz | Control : Yes | Reception range : 950 ... 2150 MHz |
| Mains adapter : external DC 12V/2A | SFI : Yes | Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 |
| | | DVB-S : QPSK |
| | | DVB-S : 2 ... 45 |
| | | DVB-S2 : 8PSK - QPSK |
| | | DVB-S2 : 2 ... 45 |
| | | FEC : Viterbi and Reed-Solomon |
| | | SCOPE OF DELIVERY |
| | | TECHNISTAR S6, remote control with batteries, external mains adapter, HDMI cable, quick start guide EN/FR/NL/CZ |



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.